

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)


PCT

(10) International Publication Number
WO 2004/109272 A1

- (51) International Patent Classification⁷: **G01N 29/02, 27/00**
- (21) International Application Number:
PCT/GB2004/002363
- (22) International Filing Date: 4 June 2004 (04.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0312818.8 4 June 2003 (04.06.2003) GB
- (71) Applicant: **CAMBRIDGE UNIVERSITY TECHNICAL SERVICES LTD [GB/GB]**; The Old Schools, Trinity Lane, Cambridge CB2 1TS (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **STEVENSON, Adrian [GB/GB]**; Cambridge University Technical Services Ltd, The Old Schools, Trinity Lane, Cambridge CB2 1TS (GB).
- (74) Agent: **GILL JENNINGS & EVERY**; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: **ELECTROMAGNETIC PIEZOELECTRIC ACOUSTIC SENSOR**



(57) Abstract: An acoustic sensor comprises at least one resonant element. A driver comprises an electrical coupling means and an electromagnetic field source arranged such that the electrical coupling means transfers currents to the electromagnetic field source. The electromagnetic field source produces an electromagnetic field that drives the resonant elements to produce acoustic waves directed to a predetermined part of a test sample. Also provided is an electromagnetic detector for receiving the acoustic spectrum omitted from a test sample and an electrical circuit connected to the drive around detector.

WO 2004/109272 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.